

# THREE STATION A.D.A. WALL MOUNTED SQUARE CORNER SERVICE SINK WITH TUBULAR SUPPORTS

## WITH/WITHOUT MANUAL FAUCETS



ltem #:	Qty #:		
Model #:			
Project #: _			





### **FEATURES:**

8 1/2" high backsplash.

5" sink bowl depth.

Two stainless steel "Z" brackets.

One K-6 3 1/2" rear basket drain.

Two tubular stainless steel support brackets that allow full clearance underneath.

Manual Operated: Six holes, 8" O.C. provided.

Faucet not included.

#### **CONSTRUCTION:**

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed tubular wall brackets.

#### **MATERIAL:**

All 16 gauge type "304" stainless steel.

1 5/8" tubular "304" stainless steel wall brackets.

Stainless steel gussets.

### **MECHANICAL:**

Faucet holes 8" on center.

		# of Faucets Sink	# of Faucets		Cu.
Model #	Length	Accommodates	Included	Wt.	Ft.
19-18-60-ADA	60"	3	0	80 lbs.	22
		(Faucets Not Included)			
19-18-60-ADA-F	60"	3	2	80 lbs.	22
		(Equanta Included)			



#### **MULTI-STATION ACCESSORIES & REPLACEMENT PARTS** Description QTY: Model **€** K-6 3 1/2" Drain (1 1/2" I.P.S.) **F** K-13 Stainless Steel Soap Dispenser (Wall Mount Only) ₩ K-06 Splash Mount Faucet Mounting Kit **K-101** 8" Swing Spout Splash Mt. Faucet K-161-LU Splash Mounted 3-1/2" Gooseneck Faucet (8" O.C.) K-159 **K-159 K-160** Splash Mounted 6" Swivel Spout Faucet (8" O.C.) K-160 **K-411** Strainer Plate for 3-1/2" Drain **K-1118** Extra H.D. 8" Splash Mounted Faucet K-316-LU Wrist Handles K-472 Faucet Hole Revision (Manual Faucet Operated Sinks Only) K-508 Special Sizing Charge (Larger Size Cut Down To Smaller Size) K-13 **TA-19** Adjustable Stainless Steel Flanged Bullet Foot

Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

MARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933

## **DETAILS and SPECIFICATIONS**

TOL ± .500" FITTINGS SUPPLIED AS SHOWN ALL DIMENSIONS ARE TYPICAL



