



REGALINE SINKS

Three & Four Compartments without Drainboards



Tile edge for ease of installation.

One piece Deep Drawn sink bowls with splash.

All sink bowls have a large liberal 3" radius.

Placement of the welded leg assembly ensures stability and furnishes direct support of the column load requirement for the entire sink unit.

"94" Series are supplied with adjustable front and rear cross brace featuring leg casting to secure left to right cross bracing.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Gussets welded to a die-embossed reinforcing channel.





Recessed Bowl Surface Accommodates Poly-Vance Cutting Boards & Sink Covers



MATERIALS:

Spec-Line (94 Series): 14 gauge type 304 stainless steel

11" High Splash.

Standard (93 Series): 16 gauge type 304 stainless steel

8" High Splash.

Super Saver (9 Series): 18 gauge type 304 stainless steel

8" High Splash.

LEGS: • 1 5/8" diameter tubular stainless steel.

• Stainless steel gussets & channels.

• Stainless Steel 1" adjustable bullet feet.

YES! It's SeaMLess!

O.A. # of			SPEC-LINE 94 Series		STANDAF	RD 93 Series	SUPER SAVE	Cu.		
Bowl Size	Length	Comp.	Model #	WT.	Model #	WT.	Model #	WT.	Ft.	
				304 S/S ter Level	16 Ga. 304 S/S 12" Water Level		18 Ga. 3 0 12" Water			
16" x 20"	62"	Three	94-3-54	142 lbs.	93-3-54	107 lbs.	9-3-54	95 lbs.	28	
	[†] 81"	Four	94-4-72	225 lbs.	93-4-72	176 lbs.	9-4-72	155 lbs.	44	
20" x 20"	74"	Three	94-23-60	232 lbs.	93-23-60	188 lbs.	9-23-60	169 lbs.	44	
	† 97"	Four	94-24-80	285 lbs.	93-24-80	210 lbs.	9-24-80	192 lbs.	56	
18" x 24"	68"	Three	94-63-54	249 lbs.	93-63-54	203 lbs.	9-63-54	188 lbs.	36	
10 X 24	89"	Four	94-64-72	312 lbs.	93-64-72	264 lbs.	9-64-72	255 lbs.	56	
24" x 24"	[†] 86"	Three	94-43-72	252 lbs.	93-43-72	213 lbs.	9-43-72	200 lbs.	56	
24 X 24	[†] 113"	Four	94-44-96	347 lbs.	93-44-96	302 lbs.	9-44-96	281 lbs.	74	
20" " 20"	74"	Three	94-83-60	255 lbs.	93-83-60	225 lbs.	9-83-60	216 lbs.	65	
20" x 28"	[†] 97"	Four	94-84-80	345 lbs.	93-84-80	310 lbs.	9-84-80	287 lbs.	78	
[†] Requires 2 Faucets			14" Water Level 17" Flood Level			er Level od Level	12" Water Level 15" Flood Level			



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Ouotes:


Email: smartfab@advancetabco.com or Fax: 631-586-2933


DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500"


Interior: ± .250"


ALL DIMENSIONS ARE TYPICAL






4 Compartment








DESCRIPTION						94 SERIES					9 & 93 SERIES						
BOWL (SIZE)	# of Compart.	Overall Length	Recommended Use	A	В	C	D	v	w	x	Y	z	v	w	x	Y	z
16x20	Three Four	62" †81"	DISH SINKS	20"	16"	13 5/8"	27"	38"	11"	14"	20"	45"	38"	8"	12"	22"	42"
20x20	Three Four	74" †97"	DISH & POT SINKS	20"	20"	13 5/8"	27"	38"	11"	14"	20"	45"	38"	8"	12"	22"	42"
18x24	Three Four	68" †89"	POT & PAN SINKS	24"	18"	15 5/8"	31"	38"	11"	14"	20"	45"	38"	8"	12"	22"	42"
24x24	Three Four	*86" †113"	POT SINKS	24"	24"	15 5/8"	31"	38"	11"	14"	20"	45"	38"	8"	12"	22"	42"
20x28	Three	74" †97"	PAN SINKS	28"	20"	17 5/8"	35"	38"	11"	14"	20"	45"	38"	8"	12"	22"	42"

^{*} Requires 2 Faucets



MECHANICAL:

- Supply is 1/2" IPS hot & cold.
- Faucet holes on 8" centers.
- Faucets are not included (see accessories).
- Waste drains are 1 1/2" IPS S/S basket type, located in center of sink bowl, and are included.



