OPUS 6434 64" x 34" x 25" (FREESTANDING)

NEW

A symphony of lines and curves inspired by the creative genius of the artist.



MODEL		TUB			
Freestanding		BOS2RF00F			
TUB Soaker			\$		
FEATURES					
Installation type		Freestanding			
No. of bathers	•	Imp. gallo	ns	68	
US gallons	81	Armrests		2	
INTEGRATED WASTE & OVERFLOW BOVERINI-XX					
White 01, Chrome 07, Brushed Nickel 09, Polished Nickel 10		Installed & Included			
STANDARD COLOR					
White 01			Included		
FINISH					
Satin Finish				Included	

OPTIONS (UPCHARGE APPLICABLE)				
INTEGRATED WASTE & OVERFLOW BOVERINI-XX				
Matte Black 19, Satin Brass 18	\$			
ISLAND TUB DRAIN™*				
Island Tub Drain [™] BISLDD	\$			
Cast Iron Island Tub Drain [™] BISLDDCI	\$			
IF REQUIRED BY CONSTRUCTION CODE OR INSTALLED WITH ITD*				
Brass waste kit BDRCB	\$			

★ An Island Tub Drain[™] and the Brass waste kit are required when there is no access under the bath.

\$

TOTAL PRICE

Made with FineStone®

FineStone[®] is a high quality solid surface material composed of refined minerals and pure acrylic. Designed with care, this material is non porous, hygienic, and thermal insulant. Its satin finish is easy to clean and will maintain its properties through time.










OPUS 6434 (FREESTANDING)

INSTALLATION







LETTER	DESCRIPTION	MEASURE
Α	Total length	64"
В	Total width	34"
с	Bathing well length	47 15/16"
D	Bathing well width	25 15/16"
E	Deck width	3/4"
F	Deck width	3/4"
G	Total maximal height	24 3/4"
н	Total minimal height	24"
I	Base length	43 1/16"
J	Slope of backrest	23°
к	Maximum water level	18 1/4"
L	Base width	20 1/16"

TECHNICA	L SPECIFICATIONS		
Other	Faucet must be freestanding or wall-mounted.	Cutting template	# 90000088
	must be installed by certified professionals only and according to our Installation Instructions as well as ncial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).	Approx. shipping weight	310 lbs
rederal, provi	ncial/state and local building codes and regulations (www.bainuitra.com/documentation/documentation).	WARRANTY	
		Bath	20 years
		* Some restrictions apply www.bainultra.com/warranty	

The specifications shown indicate the outer edge dimension and the inside bathing capacity. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.